

# TUNNEL LIGHT FIXTURE

## MFTL

### Application

Tunnels and underpass areas.

### Construction

**Body:** Anodized aluminum extruded housing. End covers of cast aluminum with silicon gasket.

**Lens:** 5 mm thick tempered glass

**Reflector:** Die formed aluminum for 5 light different distributions.

**Finish:** electrostatically deposited polyester paint powder Graphite Black color.

**Connections:** Cable Gland.

**Starting Temperature:** -20° F

**Mounting:** Tilt coupling with angle adjustment range of +/-70°



### Electrical

UL listed wire rated for required temperature and voltage. Lamps is secured with twist lock medium base.

### Warranty

One year standard warranty on fixture. Ballast carries 3-5 year manufacture warranty.

### Options

Control. (See available options)

### Features

- Graphite Black color
- UL Listed for Wet Locations
- Factory supplied lamps are available in various CRI ratings, temperature colors and rated life
- Controllable using DALI protocol.

### Ordering Information

Use the Flow chart below to configure the part number. Actual part number may vary due to configuration.

<b>MFTL</b>	<b>Type</b> TL Tunnel Light Fixture
	<b>Number of Lamps Required</b> 1 - 2 Lamp 54w T5 Fluorescent    1- 2 Lamp 32w T8 Fluorescent
	<b>Reflector</b> MS - Medium Symmetrical    IS - Intensive Symmetrical    ES - Extensive Symmetrical IA - Intensive Asymmetrical    EA - Extensive Asymmetrical
	<b>Control</b> <input type="checkbox"/> - All Lamps DALI protocol