

Parking Lot Fixture

MFLED-PLL

Application

Site, area, and general lighting utilizing advanced LED optical system providing high uniformity, excellent vertical light distribution, reduced offsite visibility, reduced on-site glare and effective security light levels.

Construction

Housing: Die-cast aluminum housing. Slim architectural Design incorporates a heat sink directly into the unit ensuring maximum heat transfer, long LED life and a reduced EPA.

LED and Optical Assembly: Optimized LED array based on distribution pattern. Utilizes High Brightness LEDs, 70 CRI at 6000K.

Life: System rating is 50K hours @ L85.

Ratings: UL/cUL listed, suitable for wet location. Rated -40°C to 50°C ambient.

Finish: Corrosion resistant polyester powder painted. Standard colors: Dark Bronze.



Electrical

Integral surge protection Class "A" Sound Rating. 120-277 voltage available with universal Electronic driver. 347V and 480V available without PE receptacle.

Warranty

Five (5) year limited warranty. Contact factory for additional information.

Options

Mounting Arms, Arm Adapters. (See available options)

Features

- 4 Optical configurations to meet all area lighting requirements.
- 4 Distribution Orientations.
- Voltage 120 - 208 / 480v Ballast
- Size (no arm): 20" wide x 28.5" long
- Mounting options for round, square and slipfitter.
- Weight: 51-57 lbs

Ordering Information

Use the Flow chart below to configure the part number. Actual part number may vary due to configuration.

MFLED-PLL	Type Parking Lot Lighting LED Fixture
	Optical Code SS - Symmetric Square CS - Symmetric Square W3 - Asymmetric Wide F4 - Asymmetric Forward Throw
	Body Color Blank - Bronze
	Options Mounting Arms, Arm Adapters, Color