

Induction Cobrahead Fixture

MFCH-IND

Application

Site, area, and general lighting utilizing Induction system providing high uniformity, excellent vertical light distribution, reduced offsite visibility, reduced on-site glare and effective security light levels.



Construction

Housing: Die Cast Construction, Hinged Front Frame with Stainless Steel Tool-Less Clips. Internal Ballast Tray.

Lens: Molded Sag Glass Lens

Reflector: Specular Aluminum Reflector

Mounting: 2 3/8" Diameter Mounting Arm

Wattage: 200w, 5000K

Ratings: CSA listed for wet location.

Finish: Smooth Gray Powdercoat Finish Over a Chromate Conversion Coating

Electrical

Integral surge protection Class "A" Sound Rating. 120 or 277 voltage.

Warranty

Five (5) years limited warranty. Contact factory for additional information.

Options

Mounting Arms, Arm Adapters. (See available options)

Features

- 1000,000 Hour System Life
- Voltage 120 or 277v Ballast
- Size (no arm): 16" wide x 36.75" long
- Instant On, Instant Restrike
- No Color Shift, No Flicker, Even Light Distribution
- Mounting accepts 2 3/8" Diameter Mounting Arm

Ordering Information

Use the Flow chart below to configure the part number. Actual part number may vary due to configuration.

MFCH-IND	Type Cobra Head Induction Head Fixture
	Ballast Voltage 120 - 120v
	Body Color Blank - Gray
	Options Mounting Arms, Arm Adapters, Color